



SAFETYFIRST

SAFETYBOX® KEMFIRE 1500/50 Type E

Data Sheet



**ASPIRATED SAFETY CABINET FOR THE COMBINED STORAGE
OF CHEMICALS, ACIDS AND BASES, AND SOLID AND LIQUID FLAMMABLES
IN COMPLIANCE WITH
EN 14470-1, EN 61010-1, EN 16121:2013/A1:2017, EN 16122:2012 NORMS - CE MARK
FIRE RESISTANCE 'TYPE 90' – 90 min.
TÜV CERTIFICATION**



- Cabinet in compliance with EN 14470-1, EN 61010-1, EN 16121:2013/A1:2017, EN 16122:2012
- Completely produced in **pickled and electrogalvanized steel** 10/10 mm painted with epoxy acid-proof powders electrostatically applied through thermic tunnel at 200°C. Smooth painting in the most delicate parts, and textured in the exposed parts. **Thickness of painting** from a minimum of **60 µm** (micron) to a maximum of **250 µm** (micron) as per UNI EN ISO 9001:2008 procedure.
- **External monolithic construction completely sealed.** New building method with double cases, internal and external.
- “Danger” stickers for corrosive, harmful and toxic products on the chemicals compartment and “No Smoking” and “Fire” warning stickers on the flammables compartment, as required by European Norms DIN 4844 and ISO 3864.
- Key lock with extractable cylinder (on demand “passe-partout kit” master key in case of lost keys)
- Grounding connection to discharge build-up of static electricity.
- Levelling feet for balance.
- **Lifetime warranty “RC PRODOTTI”:** it covers any injury to persons and objects.
- Usage and maintenance manual.
- Packaging with “Tipping over system®” device.

COMPARTMENT FOR CHEMICAL, ACID AND BASE PRODUCTS

- Watertight bottom basin in electrogalvanized steel painted with epoxy anti-acid powders with drilled shelf. Capacity approx. 4 litres.

- Door opening up to 180° to allow an easy extraction of the shelves without tilting them.
- Acid-proof hidden hinges.
- **Prepared for activated charcoal filter Carbox® (mod. F007).**
- **Termically protected electro aspirator IMQ IPX4** made of class V0 polymer to grant the highest level of self-extinguishing, in compliance with EN 60335-1, EN 60335-2-80 and EN 50366 norms.
- Input voltage: Volt 220/230.
- Max absorbed power: 65W.
- Fuse 5x20 F 500 µA.
- ON/OFF lamp.

COMPARTMENT FOR FLAMMABLE PRODUCTS

- Fire test carried out in accredited laboratories according to EN 1363-1:1999 and UNI EN 1363-1:2001.
 - New fireproof insulation made of highly fire resistant material, completely ecological.
 - **Internal body panels made of anti-scratch material, resistant to corrosive products.**
 - **Inflatable trimming 8 + 6 cm (DIN 4102)**, that swells in case of fire, isolating the inside of the cabinet from the outside.
 - **Extra inflatable trimming** with protection against “Cold and Hot fumes” and dusts.
 - Self-closing doors with automatic return.
 - **Safety closing system: in case of fire, automatically closes the door at a temperature of >50°C. Not electric.**
 - Watertight bottom basin in electrogalvanized steel painted with epoxy anti-acid powders, with drilled shelf. Collection capacity approx. 9 litres. Loading capacity kg. 80.
 - Natural internal ventilation system for vapours, equipped with two certified security valves for air recycling with automatic closure at 70 ± 10° C. The valves are positioned at the top and at the bottom of the rear wall of the cabinet in order to grant the release of substances, as per normative. External connection collar Ø 100 mm.
 - **Safety catch “Ignis-lock®”** that keeps the doors closed in case of fire.
 - Anti-spark hinges.
-
- External dimensions: (WxDxH): mm 1495 x 510 x 600
 - Internal dimensions: compartment for chemicals, acids and bases (WxDxH): mm 320 x 460 x 560
 - Internal dimensions: compartment for flammables (WxDxH): mm 936 x 355 x 440
 - Weight: kg 210 – Internal volume: approx. 85 + 146 Liters

ACCESSORIES

For chemicals compartment

- Activated charcoal filter **Carbox®** (cod. F007)